

SAFETY DATA SHEET

Version 8.8
Revision Date 07.01.2022
Print Date 07.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Tetra-n-butylammonium hydroxide solution in 2-propanol/methanol for titrations in nonaqueous media $c[(C_4H_9)_4NOH] = 0.1$ mol/l (0.1 N) Titripur® Reag. USP

Product Number : 1.09162
Catalogue No. : 109162
Brand : Millipore

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis

1.3 Details of the supplier of the safety data sheet

Company : Millipore (Canada) Ltd.
2149 Winston Park Dr. , Oakville
ONTARIO L6H 6J8
CANADA

Telephone : +1 905 829 9500
Fax : +1 905 829 9500

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA)
+1-703-527-3887 CHEMTREC
(International)
24 Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with Hazardous Products Regulations (HPR) (SOR/2015-17)

Flammable liquids (Category 2), H225
Acute toxicity, Oral (Category 4), H302
Acute toxicity, Inhalation (Category 4), H332
Acute toxicity, Dermal (Category 4), H312
Skin corrosion (Category 1), H314
Serious eye damage (Category 1), H318
Skin sensitization (Category 1), H317
Specific target organ toxicity - single exposure (Category 1), Eyes, Central nervous system, H370

Millipore - 1.09162

Page 1 of 15

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapor.

H302 + H312 + H332

Harmful if swallowed, in contact with skin or if inhaled.

H314

Causes severe skin burns and eye damage.

H317

May cause an allergic skin reaction.

H336

May cause drowsiness or dizziness.

H370

Causes damage to organs (Eyes, Central nervous system).

Precautionary statement(s)

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233

Keep container tightly closed.

P240

Ground and bond container and receiving equipment.

P241

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242

Use non-sparking tools.

P243

Take action to prevent static discharges.

P260

Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264

Wash skin thoroughly after handling.

P270

Do not eat, drink or smoke when using this product.

P271

Use only outdoors or in a well-ventilated area.

P272

Contaminated work clothing should not be allowed out of the workplace.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P312 + P330

IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

P301 + P330 + P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P311

IF exposed or concerned: Call a POISON CENTER/ doctor.

P333 + P313

If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364

Take off contaminated clothing and wash it before reuse.

P370 + P378

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P403 + P233

Store in a well-ventilated place. Keep container tightly closed.

P403 + P235

Store in a well-ventilated place. Keep cool.

P405

Store locked up.

P501

Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

- none

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Component		Classification	Concentration *
2-Propanol			
CAS-No.	67-63-0	Flam. Liq. 2; Eye Irrit. 2A;	>= 60 - < 80 %
EC-No.	200-661-7	STOT SE 3; H225, H319,	
Index-No.	603-117-00-0	H336	
Registration number	01-2119457558-25-XXXX	Concentration limits: >= 20 %: STOT SE 3, H336;	
* Weight %			
Methanol			
CAS-No.	67-56-1	Flam. Liq. 2; Acute Tox. 3;	>= 10 - < 30 %
EC-No.	200-659-6	STOT SE 1; H225, H301,	
Index-No.	603-001-00-X	H331, H311, H370	
Registration number	01-2119433307-44-XXXX	Concentration limits: >= 10 %: STOT SE 1, H370; 3 - < 10 %: STOT SE 2, H371;	
* Weight %			
Tetrabutylammonium hydroxide			
CAS-No.	2052-49-5	Acute Tox. 4; Skin Corr.	>= 1 - < 5 %
EC-No.	218-147-6	1B; Eye Dam. 1; Skin Sens. 1; H302, H314, H318, H317	
* Weight %			

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist.
Remove contact lenses.

If swallowed

After swallowing: fresh air. Make victim drink ethanol (e.g. 1 drinking glass of a 40% alcoholic beverage). Call a doctor immediately (mention methanol ingestion). Only in exceptional cases, if no medical care is available within one hour, induce vomiting (only in fully conscious persons) and make victim drink ethanol again (approx. 0.3 ml of a 40% alcoholic beverage/kg body weight/hour). Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Nitrogen oxides (NO_x)

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
2-Propanol	67-63-0	TWAEV	400 ppm 983 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	200 ppm	Canada. British Columbia OEL

		STEL	400 ppm	Canada. British Columbia OEL
		STEL	400 ppm 984 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	200 ppm 492 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEV	500 ppm 1,230 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
Methanol	67-56-1	TWA	200 ppm 262 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Substance may be readily absorbed through intact skin			
		STEL	250 ppm 328 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
	Substance may be readily absorbed through intact skin			
		TWA	200 ppm	Canada. British Columbia OEL
	Contributes significantly to the overall exposure by the skin route.			
		STEL	250 ppm	Canada. British Columbia OEL
	Contributes significantly to the overall exposure by the skin route.			
		STEV	250 ppm 328 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	Skin (percutaneous)			
		TWAEV	200 ppm 262 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	Skin (percutaneous)			
		TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	400 ppm	USA. ACGIH Threshold Limit Values (TLV)

		TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Viton®

Minimum layer thickness: 0.70 mm

Break through time: 120 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: liquid Color: colorless
b) Odor	characteristic
c) Odor Threshold	No data available
d) pH	ca.14 at 20 °C (68 °F)
e) Melting point/freezing point	No data available
f) Initial boiling point and boiling range	No data available
g) Flash point	12 °C (54 °F)
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapor pressure	No data available
l) Vapor density	No data available
m) Density	0.792 g/cm ³ at 20 °C (68 °F)
Relative density	No data available
n) Water solubility	soluble
o) Partition coefficient: n-octanol/water	No data available
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	Not classified as explosive.
t) Oxidizing properties	none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion with:

chlorates

Phosgene

organic nitro compounds

hydrogen peroxide

nitrogen oxides

perchlorates

perchloric acid

salts of oxyhalogenic acids

chromium(VI) oxide

oxyhalogenic compounds

nonmetallic oxides

chromosulfuric acid

hydrides

zinc diethyl

Halogens

Magnesium

Nitric acid

Risk of ignition or formation of inflammable gases or vapours with:

Alkali metals

Alkaline earth metals

Exothermic reaction with:

Nitric acid

Aldehydes

Amines

fuming sulfuric acid

Iron

Aluminum

Chlorine

Sodium hydrosulfide

Strong acids

Acid anhydrides

Reducing agents

acid halides

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

various plastics, various alloys, zinc alloys, Magnesium, Rubber, oils

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Acute toxicity estimate Oral - 440.61 mg/kg
(Calculation method)

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

Acute toxicity estimate Inhalation - 4 h - 10.87 mg/l - vapor (Calculation method)

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages: , damage of respiratory tract

Acute toxicity estimate Dermal - 1,341 mg/kg
(Calculation method)

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

Mixture causes serious eye damage. Risk of blindness!

Respiratory or skin sensitization

Mixture may cause an allergic skin reaction.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Mixture causes damage to organs. - Eyes, Central nervous system
Mixture may cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Components

2-Propanol

Acute toxicity

LD50 Oral - Rat - 5,840 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 37.5 mg/l - vapor

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - 12,800 mg/kg

Remarks: (RTECS)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation

(OECD Test Guideline 405)

(Regulation (EC) No 1272/2008, Annex VI)

Respiratory or skin sensitization

Buehler Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male and female - Bone marrow

Result: negative

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation, Oral - May cause drowsiness or dizziness. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Acute inhalation toxicity - Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Methanol

Acute toxicity

Acute toxicity estimate Oral - 100.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Nausea, Vomiting

Acute toxicity estimate Inhalation - 4 h - 3.1 mg/l - vapor

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300.1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

Remarks: (ECHA)

Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

Remarks: (ECHA)

Respiratory or skin sensitization

Sensitisation test: - Guinea pig

Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male and female - Bone marrow

Result: negative

Carcinogenicity

Did not show carcinogenic effects in animal experiments.

Reproductive toxicity

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Causes damage to organs. - Eyes, Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Acute oral toxicity - Nausea, Vomiting

Acute inhalation toxicity - Irritation symptoms in the respiratory tract.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Tetrabutylammonium hydroxide

Acute toxicity

LD50 Oral - Rat - female - 1,000 mg/kg
(OECD Test Guideline 423)

Inhalation: No data available

Dermal: No data available

Skin corrosion/irritation

Causes skin burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

Components

2-Propanol

Toxicity to fish	flow-through test LC50 - Pimephales promelas (fathead minnow) - 9,640 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 13,299 mg/l - 48 h Remarks: (IUCLID)
Toxicity to algae	IC50 - Desmodesmus subspicatus (green algae) - > 1,000 mg/l - 72 h Remarks: (IUCLID)
Toxicity to bacteria	EC5 - Pseudomonas putida - 1,050 mg/l - 16 h Remarks: (Lit.)

Methanol

Toxicity to fish	flow-through test LC50 - Lepomis macrochirus (Bluegill) - 15,400.0 mg/l - 96 h (US-EPA)
Toxicity to daphnia and other aquatic invertebrates	semi-static test EC50 - Daphnia magna (Water flea) - 18,260 mg/l - 96 h (OECD Test Guideline 202)
Toxicity to algae	static test ErC50 - Pseudokirchneriella subcapitata (green algae) - ca. 22,000.0 mg/l - 96 h (OECD Test Guideline 201)
Toxicity to bacteria	static test IC50 - activated sludge - > 1,000 mg/l - 3 h (OECD Test Guideline 209)

Tetrabutylammonium hydroxide

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned

containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

TDG

UN number: 2924 Class: 3 (8) Packing group: II
Proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (2-Propanol, Methanol)
Subsidiary risk : 8
Labels: 3
(8)ERG Code: 132
Marine pollutant: no

IMDG

UN number: 2924 Class: 3 (8) Packing group: II EMS-No: F-E, S-C
Proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (2-Propanol, Methanol)

IATA

UN number: 2924 Class: 3 (8) Packing group: II
Proper shipping name: Flammable liquid, corrosive, n.o.s. (2-Propanol, Methanol)

SECTION 15: Regulatory information

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.8

Revision Date: 07.01.2022

Print Date: 07.01.2022